



12.5 mm PMI® EZ Bend™ Hudson Classic Professional Rope with Unicore®



Designed for rugged or harsh environments, this 12.5 mm rope has high abrasion resistance for real-world application to suit any professional. Unicore® technology creates the ultimate bond between sheath and core. This bond ensures sheath slippage is nearly zero, even when the sheath is entirely cut circumferentially. This rope allows the firefighter or rope technician to pass either a cut or torn sheath area, whether descending or ascending, since the sheath cannot bunch to create an impasse.

Key Features

- Unicore® technology
 - 16-carrier construction
 - Nearly zero sheath slippage
 - CI 1801 Certified
 - NFPA Certified
 - Torsionally balanced, continuous filament nylon
-

Additional Information

Shipping weight | N/A

Color | Blue/White/Orange, Orange/White/Blue, Red/White/Blue

Brand | [PMI](#)

Length | 183 m (600 ft), 46 m (150 ft), 61 m (200 ft), 92 m (300 ft)

Weight | 107 g/m

MBS | 44.5 kN (10,009 lbf)

Elongation at 1.35 kN (300 lbf) | 0.7%

Elongation at 2.7 kN (600 lbf) | 1.6%

Elongation at 4.45 kN (1000 lbf) | 3.5%

Elongation at 8.0 kN (1800 lbf) | 6.3%

Elongation at 10% MBS | 3.0-4.4%

Compliant | ANSI Z359.15, EN 1891-A, NFPA 2500 (1983) 2022 ED (G)

Tags

[Confined Space](#), [Fall protection](#), [Fire Rescue](#), [Rope Access](#), [Rope Rescue](#), [Ropes Course](#), [Tower](#), [Wilderness Rescue](#)

Product Code

RR125US046UC | Red/White/Blue | 46 m (150 ft)
RR125US061UC | Red/White/Blue | 61 m (200 ft)
RR125US092UC | Red/White/Blue | 92 m (300 ft)
RR125US183UC | Red/White/Blue | 183 m (600 ft)
RR125OW046UC | Orange/White/Blue | 46 m (150 ft)
RR125OW061UC | Orange/White/Blue | 61 m (200 ft)
RR125OW092UC | Orange/White/Blue | 92 m (300 ft)
RR125OW183UC | Orange/White/Blue | 183 m (600 ft)
RR125BW046UC | Blue/White/Orange | 46 m (150 ft)
RR125BW061UC | Blue/White/Orange | 61 m (200 ft)
RR125BW092UC | Blue/White/Orange | 92 m (300 ft)
RR125BW183UC | Blue/White/Orange | 183 m (600 ft)

