



PMI® 3/4" Toggle Lok Anchor Hardware | Anchorage Connectors



This innovative anchor sets itself apart from the competition. It features unmatched safety, ease of use, and versatility. This anchor can be removed and used again. The Toggle works in horizontal, vertical, and overhead surfaces. It also works in either precast concrete or steel flanges. Costly engineering inserts are not required. This anchor can be used for fall protection, life line systems, restraint, work positioning, tie back anchors, and more.

Key Features

- Works in both shear and tensile loads
- Spring is zinc plated steel
- Swage is zinc plated copper
- Hole plug is aluminum alloy
- Cable sheath is plastic
- Main cable is 7 x 19 galvanized cable

Additional Information

Shipping weight | 0.6 lbs

MBS | 50 kN (11240 lbf)

Height | 0.50" (1.3 cm)

Length | 7.00" (17.8 cm)

Weight | 11.4 oz (323 g)

Compliant | ANSI Z359.1 (2007), EN 795

Tags

[fall protection](#), [made in USA](#), [Spring is zinc plated steel](#), [Main cable is 7 x 19 galvanized cable](#), [3/4" Toggle Lok Removable anchor](#), [For hollow concrete and steel](#), [22 kN](#), [Swage is zinc plated steel](#), [Rope Rescue](#), [Confined Space](#), [Rope Access](#)

Product Code

HD26225

