



Flexible Sided Ladders 6" Aluminum Rungs, 4 mm Galvanized Cable Brand | Lyon Equipment



Flexible sided ladders are a cost effective, lightweight solution for temporary access to confined spaces and difficult to reach locations. Even with minimal training, ladders can easily be transported and rapidly deployed for use. Personnel utilizing ladders should always use a separate fall protection system for safety.

Construction: The rungs are hollow tubes with a dowel insert. Rungs are secured to the side wire ropes with pins and resin. A pin is driven through the center of the rope into the dowel and set in resin to form a solid block inside the rung. A plastic cap is then pushed in to seal the rung end. Black rungs are cut to size and drilled before treatment to ensure that the alloy tube is 100% anodized. **Compact Ladders:** General purpose ladder for ascending/descending. Used for applications such as manhole entry, caving, and access to lighting truss. With fitness and a little practice, they are easy to climb.

Key Features

- Standard lengths are 5 m and 10 m
 - Easy to carry and store
 - Two rung spacing options
 - Requires a separate fall protection system
 - Other lengths made to order
 - Swaged eye ends
 - Rungs are 6.0" wide
 - Can be connected together for longer lengths
 - Accessories available
 - Aluminum rungs are 0.50" Diameter
-

Additional Information

Shipping weight | 2.86 lbs

Length | 10 m long w/ 30 cm Rung Spacing, 10 m long w/ 25 cm Rung Spacing

Brand | [Lyon Equipment](#)

Size | 6"

Weight | 2.87 lbs (1.300 kg), 5.73 lbs (2.600 kg)

Product Code

LD39003 | 10 m long w/ 30 cm Rung Spacing

LD39001 | 10 m long w/ 25 cm Rung Spacing

