



SMC/RA 4" Double Stainless Steel Pulley, NFPA-G PMI Outlet |



Based on Russ Anderson's original design - that are legendary throughout the fire, rescue and work-related professions. - these pulleys are essential equipment for the serious rigger. The SMC/RA 4" Double Stainless Steel Pulley rotating side plates allow attachment of the pulley anywhere on the rope and will accept multiple carabiners. Axle nuts are marked with a blue witness line to indicate if the axle nut has been turned or tampered with. **Please note that all PMI Outlet items have limited stock.**

Key Features

- UL Certified to NFPA1983 "G" General Use.
 - Uses either high efficiency sealed ball bearings or durable Oilite bushings and are designed to work flawlessly under conditions that might shut down a lower quality pulley.
 - Matched double-bend side plates help eliminate compression under load.
 - Sealed ball bearings provide optimal efficiency thus reducing the performance robbing resistance inherent in most multiple component systems and are not prone to failure under misaligned loads or with twisted gear as may occur with needle bearings.
 - The axle-nuts are double locked to the steel axle and marked with a witness line to help detect any loosening.
-

Additional Information

Shipping weight | 2.7 lbs

Type | Ball Bearing, Oilite

Brand | [SMC](#)

MBS | 63 kN (14,163 lbf)

Height | 2.40" (6.1 cm)

Length | 9.90" (25.1 cm)

Width | 4.60" (11.7 cm)

Weight | 2.52 oz (1.142 kg)

Sheave | 4.00"

Tread | 3.33"

Compliant | BERRY COMPLIANT, NFPA 1983 (2017), G

Tags

[Fire Rescue](#)

Product Code

SM157500N | Ball Bearing

SM157000N | Oilite

