



ISC D5PRO Work/Rescue Descender without Panic Brake



The standard D5™ Work/Rescue Descender has proven to be a popular Descender for the North American Fire & Rescue and Tower Climbing markets, which typically use 1/2" (12.7mm) ropes. Feedback gathered from highly qualified and experienced 'Pro' users highlighted a demand for a device which does not incorporate a panic-brake function. Enter the **D5PRO**! The D5PRO Work/Rescue Descender is the same great Work/Rescue Descender, but without the panic brake. This can be particularly useful on longer descents and in rescue/belay applications, where a broader 'sweet spot' is welcomed. As the **D5PRO** does not incorporate a panic-brake, it is not possible for the device to fully meet the criteria of NFPA and ANSI Standards. The D5PRO is fully certified to EN 12841 (a panic brake is not a compulsory criteria of this standard). *Note: If you require a Descender which fully meets NFPA/ANSI standards, please see the [ISC D5™ Work/Rescue Descender](#), with incorporated panic-brake.*

[DECLARATION OF CONFORMITY](#)

Key Features

- Compatible with rope diameter (12.7mm)
 - Number of persons: 2
 - ANSI compliant version: No
 - Body Material: Aluminium
 - Finish: Anodized
-

Additional Information

Shipping weight | 2.173 lbs

Color | Green/Black, Red/black

Weight | 818g (29oz)

Rated Load | 240kg (529lb)

Sizing Info | 12.7mm (1/2")

Compliant | EN12841

Tags

[Arborist](#), [Fire Rescue](#), [Rope Access](#), [Rope Rescue](#), [Wilderness Rescue](#)

Product Code

HD26290

