



Cordage Meter



Conforms to National Bureau of Standards H-44 Requirements 1969.

NOT RECOMMENDED FOR WIRE MEASURING.

NO-SLIP toothed wheel made of sintered iron keeps sure contact with cordage. NO-SAG guide trough controls cordage travel in/out. Accurately measures cordage from 5/32" to 3/4" diam. Easy feed-through because you can see and reach cordage running under polished stainless steel pressure shoe. ANALOG COUNTER indicates feet and inches to 999'11" and starts over. Also subtracts. FAST RESET: one knob returns all numbers to zero. ****PMI current catalog and Manufacturer website says Digital but its Analog***

Key Features

- Model: 1430
 - Resets to ZERO with one turn of knob
 - Conforms to weights and measures specifications in USA and Canada
 - Indicates to 999.9 m
 - Measurer should be firmly mounted for optimum accuracy
 - Analog counter adds or subtracts
 - Measurer accommodates ropes and cordage from 6 to 20 mm
-

Additional Information

Shipping weight | 3.3 lbs

Compliant | National Bureau of Standards H-44 Requirements 1969

Material | Not recommended for wire, Rope

Measurement by | Feet, Meters

Rope Diameter | 5/32" to 3/4"

Tags

[Arborist](#), [Rope Access](#), [Rope Rescue](#), [Tower](#)

Product Code

RC48003 | Feet

RC48004 | Meters

