



PMI® Deuer Steel Anchor strap

PMI |



The PMI® Deuer Steel Anchor Strap is a premium anchorage connector tailored for the specific needs of rescuers, cavers, climbers, and rope access technicians. With a robust rating of 6000 lbf, it ensures maximum safety and reliability. This strap meets the standards of ANSI Z359.18/ANSI Z459.1 and is ANSI-rated for the co-worker rescue requirement of 3,000lbf. The strap complies with multiple ANSI standards, including ANSI A10.48, ANSI Z359.18, ANSI Z359.4, ANSI Z359.7, and ANSI Z459.1. Additionally, it adheres to OSHA CFR 1926.503 and CFR1910.66 regulations. It's available in lengths of 3 ft and 6 ft and has a Minimum Breaking Strength (MBS) of 6000 lbf with a Working Weight Limit (WWL) of 640 lbf for rescue loads.

Key Features

- 6000 lbf rated
- Meeting both ANSI Z359.18/ANSI Z459.1
- ANSI rated for co-worker rescue requirement of 3,000lbf
-

Additional Information

Shipping weight | N/A

Length | 3 ft, 6 ft

Compliant | ANSI A10.48, ANSI Z359.18, ANSI Z359.4, ANSI Z359.7, ANSI Z459.1, OSHA CFR 1926.503: CFR1910.66

MBS | 6000 lbf w/ WWL of 640 lbf for Rescue loads

Tags

[Fall protection](#), [Rope Access](#)

Product Code

DD26238 | 3 ft

DD26239 | 6 ft

