



12.5 mm PMI® Sewn Eye



PMI uses precision stitching to create a permanent, sewn termination that is stronger than any knotted termination and nearly as strong as the rope itself. Heat shrink tubing protects the stitching and the label from abrasion. PMI can sew either one or two end terminations on the following ropes and these are certified as Manufacturer Supplied Eye Terminations per NFPA 2500 (2022).

Key Features

- Streamlined permanent termination
- No knots
- Nearly as strong as the rope
- Stronger than knots
- Two separate but equal blocks of stitching provide greater safety

Additional Information

Shipping weight | N/A

Diameter | 12.5 mm

Brand | [PMI](#)

of Ends | One End, Two Ends

MBS | 34.2 kN (7,684 lbf — Hudson Classic Pro with Unicore), 34.7 kN (7,806 lbf — Hudson Classic Professional)

Compliant | ANSI Z359.15 (WITH 11 MM PMI® HUDSON CLASSIC PROFESSIONAL OR PMI® EXTREME PRO), MBS 43.3 KN (9734 LBF — PMI® HUDSON CLASSIC PRO EZ), NFPA 2500 (1983)

Tags

[Arborist](#), [Fall protection](#), [Made in USA](#), [Rope Access](#), [Ropes Course](#), [Tower](#)

Product Code

KT36083 | Two Ends

KT36080 | One End

