



12.5 mm PMI® Sewn Eye



PMI® uses precision stitching to create a permanent, sewn termination that is stronger than any knotted termination and nearly as strong as the rope itself. Heat shrink tubing protects the stitching and the label from abrasion. Add these NFPA 2500 (2022) certified terminations to the [12.5 mm PMI® EZ Bend™ Hudson Classic Professional Rope](#). Also available for [9 mm](#), [10 mm](#), or [11 mm](#) PMI® Hudson Classic Professional EZ-Bend™ ropes.

Key Features

- Streamlined permanent termination
- No knots
- Nearly as strong as the rope
- Stronger than knots
- Two separate but equal blocks of stitching provide greater safety

Additional Information

Shipping weight | N/A

of Ends | One End, Two Ends

Brand | [PMI](#)

Compliant | ANSI Z359.15 (WITH 11 MM PMI® HUDSON CLASSIC PROFESSIONAL OR PMI® EXTREME PRO), MBS 43.3 KN (9734 LBF — PMI® HUDSON CLASSIC PRO EZ), NFPA 2500 (1983)

Diameter | 12.5 mm

MBS | 34.2 kN (7,684 lbf — Hudson Classic Pro with Unicore), 34.7 kN (7,806 lbf)

Tags

[Arborist](#), [Fall protection](#), [Made in USA](#), [Rope Access](#), [Ropes Course](#), [Tower](#)

Product Code

KT36083 | Two Ends

KT36080 | One End

