



PMI uses precision stitching to create a permanent, sewn termination that is stronger than any knotted termination and nearly as strong as the rope itself. Heat shrink tubing protects the stitching and the label from abrasion. PMI can sew either one or two end terminations on the following ropes and these are certified as Manufacturer Supplied Eye Terminations per NFPA 2500 (2022).

Key Features

- Streamlined permanent termination
- Stronger than knots
- No knots
- Two separate but equal blocks of stitching provide greater safety
- Nearly as strong as the rope

Additional Information

Shipping weight | N/A

Diameter | 11 mm

Brand | PMI

of Ends | One End, Two Ends

Compliant | ANSI Z359.15 (WITH 11 MM PMI® HUDSON CLASSIC PROFESSIONAL OR PMI® EXTREME PRO),

NFPA 2500 (1983) 2022 ED (T) (WITH 11 MM PMI® HUDSON CLASSIC PROFESSIONAL OR PMI® EXTREME PRO)

MBS | 36.2 kN (8,132 lbf — 11 mm Extreme Pro with Unicore), 36.2 kN (8,132 lbf — Hudson Classic Professional or Patriot Vertical Lifeline)

Tags

Arborist, Fall protection, Made in USA, Rope Access, Ropes Course, Tower, Utilities

Product Code

KT36084 | One End KT36085 | Two Ends

