



12.5 mm (1/2") PMI® Hoistmaster



A new standard in tower rigging. Whether you're hauling heavy loads or working a site, this 1/2" line is engineered for the harshest conditions you'll face. High strength, low stretch Unicore® technology outperforms traditional double-braids in durability, reliability, and minimal rotation in abrasive lifting environments. By bonding the core and sheath, we've eliminated the risks that come with traditional ropes.

WARNING

This product is a utility rope and is not rated or intended for life-safety, human support, fall protection, rappelling, climbing, rescue, or any application where failure could result in injury or death.

Key Features

- Low stretch
- Sheath: 100% Polyester
- Unicore® technology
- Core: 100% Nylon 6.6
- Minimal rotation
- 3-Sigma MBS: 10,431 lbf

Additional Information

Shipping weight | 12.36 lbs

Color | Red/Blue

Brand | [PMI](#)

Diameter | 12.5 mm, 1/2"

Length | 183 m (600 ft), 92 m (300 ft)

Material | Nylon, Nylon 6.6, Polyester

MBS | 46.4kN (10,431 lbf)

Elongation at 1.35 kN (300 lbf) | 1.3%

Elongation at 2.7 kN (600 lbf) | 2.4%

Elongation at 4.45 kN (1000 lbf) | 4.6%

Compliant | ASME B30

Weight | 1.15 oz per foot

Tags

[Confined Space](#), [Fire Rescue](#), [Rope Rescue](#), [Tower](#)

Product Code

UR125BR600UC | Red/Blue | 183 m (600 ft)

UR125BR300UC | Red/Blue | 92 m (300 ft)

