



12.5 mm PMI® Dura-Shield General Use Rope

PMI |



The Dura-Shield Tech rope is an excellent choice for rope access work or for anyone needing rope with superior sheath abrasion and heat-resistant properties such as those performing work at bridges, dams, towers, or industrial sites. If there is a chance your rope may contact a sharp edge, hot pipes, or anything hot nearby, consider this rope for the job. The sheath is 100% Technora® featuring a high tensile strength, good fatigue resistance, heat resistance, excellent dimensional stability, and chemical resistance.

Key Features

- | | | |
|--|-------------------------|---|
| • Sheath - 100% Technora® | • Core - 100% Nylon 6.6 | • High modulus of elasticity |
| • Low creep | • Low thermal shrinkage | • Thermal decomposition threshold 500°C (932°F) |
| • Can be used for long periods at a temperature of 250°C (482°F) | | |
-

Additional Information

Shipping weight | 48 lbs

Color | Natural Gold

Length | 183 m (600 ft), 46 m (150 ft), 92 m (300 ft)

Weight | 110.9 g/m

MBS | 44.2 kN (9944 lbf)

Elongation at 300 lbf | 2.5%

Elongation at 600 lbf | 5.0%

Elongation at 1000 lbf | 7.6%

Elongation at 10% MBS | 8.8%

Compliant | CI 1801, LOW STRETCH, NFPA 1983 (2012), G

Tags

[Made in USA](#)

Product Code

HS125TG183A

