



9 mm PMI® Hudson Classic Professional Rope EZ-Bend™



PMI®'s 9mm Classic Professional exhibits an exceptional level of abrasion resistance, balancing strength, and weight and ensuring superior performance in tough conditions. Add a [sewn eye](#) to create a permanent, sewn termination that is stronger than any knotted termination and nearly as strong as the rope itself. Also available in [10 mm](#), [11 mm](#), [12.5 mm](#), and [16 mm](#).

Key Features

- NFPA Certified
 - Torsionally balanced, continuous filament nylon
 - 16 carrier construction
 - Available in many colors
 - CI 1801
 - EZ-Bend construction
-

Additional Information

Shipping weight | N/A

Brand | [PMI](#)

Color | Orange/Black, White/Black

Compliant | CI 1801, EN 1891-A

Diameter | 9 mm

Elongation at 1.35 kN (300 lbf) | 3.7%

Elongation at 2.7 kN (600 lbf) | 5.4%

Elongation at 4.45 kN (1000 lbf) | 7.6%

Elongation at 10% MBS | 4.3%

Knotability | 0.6%

Length | 183 m (600 ft), 200 m (656 ft), 30 m (100 ft), 46 m (150 ft), 61 m (200 ft), 92 m (300 ft)

MBS | 18.3 kN (4,114 lbf)

Sheath Content | 49.0%

Weight | 53 g/m

Tags

[Arborist](#), [Cave Rescue](#), [Confined Space](#), [Fall protection](#), [Fire Rescue](#), [Rope Access](#), [Rope Rescue](#), [Ropes Course](#), [Tower](#), [Utilities](#), [Wilderness Rescue](#)

Product Code

RR090WB200E | White/Black | 200 m (656 ft)
RR090WB046E | White/Black | 46 m (150 ft)
RR090WB030E | White/Black | 30 m (100 ft)
RR090WB061E | White/Black | 61 m (200 ft)
RR090WB092E | White/Black | 92 m (300 ft)
RR090WB183E | White/Black | 183 m (600 ft)
RR090OB030E | Orange/Black | 30 m (100 ft)
RR090OB046E | Orange/Black | 46 m (150 ft)
RR090OB061E | Orange/Black | 61 m (200 ft)
RR090OB092E | Orange/Black | 92 m (300 ft)
RR090OB183E | Orange/Black | 183 m (600 ft)
RR090OB200E | Orange/Black | 200 m (656 ft)

