



12.5 mm PMI® Hudson Classic Old Glory EZ Bend™ with Unicore®



Show your colors with OLD GLORY. Made in the USA (of course) and certified to NFPA 2500 (1983) 2022 ED (G), this 12.5 mm rope is built for rescue. Unicore® technology creates the ultimate bond between sheath and core. This bond ensures sheath slippage is nearly zero, even when the sheath is entirely cut circumferentially. This rope allows the firefighter or rope technician to pass either a cut or torn sheath area, whether descending or ascending, since the sheath cannot bunch to create an impasse.

Key Features

- Unicore® technology
- 16-carrier construction
- Nearly zero sheath slippage
- CI 1801 Certified
- NFPA Certified
- Torsionally balanced, continuous filament nylon

Additional Information

Shipping weight | N/A

Color | Red/White/Blue

Brand | [PMI](#)

Length | 183 m (600 ft), 46 m (150 ft), 61 m (200 ft), 92 m (300 ft)

Weight | 107 g/m

MBS | 44.5 kN (10,009 lbf)

Elongation at 1.35 kN (300 lbf) | 0.7%

Elongation at 2.7 kN (600 lbf) | 1.6%

Elongation at 4.45 kN (1000 lbf) | 3.5%

Elongation at 8.0 kN (1800 lbf) | 6.3%

Elongation at 10% MBS | 3.0–4.4%

Compliant | CI 1801, NFPA 2500 (1983) 2022 ED (G), STATIC ANSI Z359.15

Tags

[Confined Space](#), [Fire Rescue](#), [Rope Access](#), [Rope Rescue](#), [Tower](#), [Utilities](#), [Wilderness Rescue](#)

Product Code

RR125US046UC | Red/White/Blue | 46 m (150 ft)
RR125US061UC | Red/White/Blue | 61 m (200 ft)
RR125US183UC | Red/White/Blue | 183 m (600 ft)
RR125US092UC | Red/White/Blue | 92 m (300 ft)

