



13 mm PMI® Isostatic Polyester Rope PMI |



A PMI signature rope constructed of 100% polyester core and sheath. These ropes are specifically designed with super low elongation for specialty applications such as highlines and applications where professional rope technicians require absolute minimal elongation. These ropes are also engineered to stay rounder and have less sheath slippage than conventional kernmantle polyester ropes.

Key Features

- NFPA Certified
 - Resists flattening under load
 - 32 carrier construction
 - 100% polyester construction
-

Additional Information

Shipping weight | N/A

Color | Blue/White/Green, Orange/White/Green

Length | 183 m (600 ft), 200 m (656 ft), 30 m (100 ft), 46 m (150 ft), 61 m (200 ft), 92 m (300 ft)

Weight | 125 g/m

MBS | 45.9 kN (10318 lbf)

Elongation at 300 lbf | 1.2%

Elongation at 600 lbf | 1.6%

Elongation at 1000 lbf | 2.1%

Elongation at 10% MBS | 1.4–2.2%

Compliant | NFPA 1983 (2012), G

Tags

[Cave Rescue](#), [Confined Space](#), [Fire Rescue](#), [Made in USA](#), [Rope Access](#), [Rope Rescue](#), [Ropes Course](#), [Tower](#), [Utilities](#), [Wilderness Rescue](#)

Product Code

PR130BG030PP | Blue/White/Green | 30 m (100 ft)
PR130BG046PP | Blue/White/Green | 46 m (150 ft)
PR130BG061PP | Blue/White/Green | 61 m (200 ft)
PR130BG061PP | Blue/White/Green | 61 m (200 ft)
PR130BG092PP | Blue/White/Green | 92 m (300 ft)
PR130BG183PP | Blue/White/Green | 183 m (600 ft)
PR130BG200PP | Blue/White/Green | 200 m (656 ft)
PR130OG030PP | Orange/White/Green | 30 m (100 ft)
PR130OG046PP | Orange/White/Green | 46 m (150 ft)
PR130OG061PP | Orange/White/Green | 61 m (200 ft)
PR130OG092PP | Orange/White/Green | 92 m (300 ft)
PR130OG183PP | Orange/White/Green | 183 m (600 ft)
PR130OG200PP | Orange/White/Green | 200 m (656 ft)

