

An incredible new PMI rope for Fire/Rescue professionals, the Classic Pro with Unicore® technology is now available in a 12.5mm (1/2") diameter! Unicore® technology creates the ultimate bond between sheath and core. This bond ensures sheath slippage is nearly zero, even when the sheath is entirely cut circumferentially. This rope allows the firefighter or rope technician to pass either a cut or torn sheath area, whether descending or ascending, since the sheath cannot bunch to create an impasse.

**Key Features:**

- Unicore® technology
- Nearly zero sheath slippage
- NFPA Certified
- 16-carrier construction
- CI 1801 Certified
- Torsionally balanced, continuous filament nylon
- Made in the USA

**12.5 mm (1/2")**

*Weight:* 107 g/m » *MBS:* 44.5 kN (10009 lbf)  
*Elongation:* 0.7% at 300 lbf | 1.6% at 600 lbf | 3.5% at 1000 lbf  
*Elongation at 10% MBS:* 3.0%-4.4%



	<b>Blue/White/Orang</b>	<b>Orange/White/Blue</b>
46 m (150 ft)	RR125BW046UC	RR125OW046UC
61 m (200 ft)	RR125BW061UC	RR125OW061UC
92 m (300 ft)	RR125BW092UC	RR125OW092UC
183 m (600 ft)	RR125BW183UC	RR125OW183UC
> 183 meter	RR125BW001UC	RR125OW001UC



**CERTIFIED** NFPA 1983 (2017), G ANSI Z359.15 CI1801, Static  
**COMPLIANT** EN 1891-A



A large, empty rectangular box with a thin black border, intended for handwritten notes.