

This mid-sized PMP is the perfect choice for rigging with 11 mm (7/16") rope or when you don't have room for a 3" PMP. Pulley will accommodate up to 13 mm rope.

Key Features:

Precision machined aluminum side plates and 2" sheaves • Sealed Bearings • Double pulleys include a bucket

Single

Height: 1.37" (3.5 cm) » Width: 2.90" (7.4 cm) »
 Length: 3.97" (10.1 cm) » Weight: 6.3 oz (179 g) »
 MBS: 36 kN (8093 lbf) » Tread: 1.49" » Axle: Ball Bearing »
 Sheave Material: Aluminum » Sheave: 2.00" »
 Max Rope Size: 13 mm

Green/Black (left) SM152700N
 Black (right) SM152701N

USA MADE BERRY COMPLIANT CERTIFIED NFPA 1983 (2012), G



Double

Height: 2.20" (5.6 cm) » Width: 2.90" (7.4 cm) »
 Length: 5.10" (13.0 cm) » Weight: 10.4 oz (295 g) »
 MBS: 46 kN (13341 lbf) »
 Bucket MBS: 23 kN (5171 lbf) » Tread: 1.49" »
 Axle: Ball Bearing » Sheave Material: Aluminum »
 Sheave: 2.00" » Max Rope Size: 13 mm

Green/Grey (left) SM152800N
 Black (right) SM152801N

USA MADE BERRY COMPLIANT CERTIFIED NFPA 1983 (2012), G



A large, empty rectangular box with a thin black border, intended for handwritten notes or technical drawings.

Pigeon Mountain Industries, Inc. | PO Box 803, LaFayette, GA 30278 | Fax: 706-764-1531 | Email: custserv@pmirope.com