

Instructions > PMI Bucket Belt



The PMI Bucket Belt (Ladder Belt) is designed especially for fall prevention of workers in bucket trucks, and should be rigged to prevent any possibility of a fall.

SG51123

Weight: 2.1 lbs (953 g)

USE GUIDELINES

- Belt should be allocated to single user.
- Adjust the Belt as necessary to perform properly with different clothing.
- Keep Belt from contact with harsh chemical or corrosive substances.
- Avoid excessive abrasion.
- Compatibility with other equipment must be verified by user.
- Repair or modification of this product without manufacturer's expressed written consent is strictly forbidden.

CAUTION

Inspect Belt upon receipt to ensure that it has not been damaged during shipment and to verify that the buckles are working properly.

INTENDED USE

Proper Belt maintenance is essential for maximum performance and safety:

- Store Belt loosely packed in a clean, dry environment.
- A wet Belt should be thoroughly dried before storage.
- Do not expose the Belt to direct flame or high temperature.
- Do not expose the Belt to chemicals or damaging substances.
- Belt may be hand washed in cool water. Use clear water or non detergent cleanser, and rinse thoroughly.

Inspect Belt before and after each use, paying special attention to load bearing buckles and components. Inspection criteria should be established by the user according to his needs, and must consider at least the following hazards:

- Missing or torn components.
- Improperly functioning buckles or attachment points.
- Webbing and/or stitching that shows excessive wear.
- Chemical damage or exposure.
- Heat damage.

WARNING

Failure to comply with these instructions and information contained in this booklet may result in injury and death.

INSTRUCTIONS

- Wear the Belt over uniform clothing as appropriate.
- Connect the small snap hook (sewn to the waist belt) to the V shaped adjustable buckle over the waist belt webbing.
- Pull or loosen the tail of the webbing to attain a secure and comfortable fit.
- Belt must be worn snug around the waist to provide the best security.
- Excess webbing must be tucked out of the way with the elastic loop on the belt.
- The orange lanyard with the large Snap Hook is designed as the primary connection point. Connect this Snap Hook to suitable anchor up to 5/8" diameter.
- User must ensure that the anchorage is appropriately located and sufficiently strong to prevent the wearer from falling.
- The Belt can be rotated around the waist to position the tether to ensure appropriate fall protection.
- For maximum protection, keep the orange tether unobstructed between the anchorage and the wearer.
- When not in use, it is advised to clip the large snap hook at the end of the orange lanyard to one of the D-rings. Never connect a lanyard or the like between the belt's tether and the anchor since the greater length may allow a fall.

The two D-ring buckles on each side of the orange lanyard are designed as secondary attachment points for additional anchorage straps, lanyards, etc.

- As a general rule, use them only in addition to the primary attachment lanyard and large snap hook.
- It is the user's responsibility to ensure that any equipment attachment to these D-rings is compatible with the size of the D-ring and will provide the needed support.

PMI LIMITED WARRANTY

PMI products are warranted to the original retail purchaser to be free from defect in material and workmanship for a period of one year. PMI will repair or replace the item without charge provided inspection at our factory discloses no misuse or alteration, which, in our judgment, has affected the condition or functioning of the product. All implied warranties imposed by law in connection with the sale of PMI products are also limited in duration to a period of one year. PMI expressly excludes and shall not be liable for any consequential damages arising out of any breach of the express or implied warranties on sales of PMI products. Because of the high risks involved in high angle rope work such as, but not limited to, rescue, rope access, caving, rappelling, rock climbing and mountaineering, no further warranties exist or are implied by PMI. Regulations issued under the Magnuson-Moss Warranty Act require us to include the following statement: some states do not allow limitations on how long an implied warranty lasts nor the excluding or limitation of incidental or consequential damages, so the above limitations may not apply to you.

