

Instructions > PMI Chest Roller Harness



A stand alone chest harness for mounting either the single or double PMI Chest Roller assembly.

Weight: 1.2 lbs (544 g)

MAINTENANCE AND CARE

Proper harness maintenance is essential for maximum performance and safety.

- Store harness loosely packed in a clean, dry environment.
- A wet harness should be thoroughly dried before storage.
- Do not expose the harness to direct flame or high temperature.
- Do not expose the harness to chemicals or damaging substances.
- Harness may be hand washed (gentle) in cool water. Use clear water or a non-detergent cleanser, and rinse thoroughly.

Inspection criteria should be established by the user according to his needs, and must consider at least the following hazards:

- Missing or torn components
- Improperly functioning buckles or attachment points
- Webbing and/or stitching that shows excessive wear
- Chemical damage or exposure
- Heat damage

INSPECTION

Inspect Harness before each use. Remove the harness from service and destroy if it does not pass inspection or if there is any doubt about the safety or serviceability of the harness. If any of the following conditions are true, the harness must be discarded:

- If the harness has sustained a significant fall (ie, fall factor 1 or greater).
- If the load bearing components of the harness are damaged in any way.
- If the stitching shows excessive wear, is cut, or is otherwise affected in a way that might affect harness function or performance.
- If buckles or attachment points do not function properly, or show signs of excessive wear or damage that might affect harness function or performance.
- If webbing is not properly rigged, or shows damage or dysfunction that might affect harness performance.
- If the harness has been visibly damaged by heat, chemical or other hazardous condition.
- If the harness has been in use for 5 years, regardless of condition.

WARNING



Failure to comply with the instructions and information contained in this booklet may result in injury or death.

HARNESS FIT

To ensure a good fit, user must try on and adjust appropriately prior to use.

- Loosen shoulder straps, and buckles attached to the Chest Roller.
- Place Harness over your head, and slide arms through the shoulder straps.
- Tighten front strap until it is snug around your chest
- Adjust shoulder straps so the height harness is appropriate.

SIZING

	Chest Circumference
Standard	30"- 40"
Large	40"- 50"

USE GUIDELINES

- Harness should be allocated to a single user.
- Keep harness from contact with harsh chemicals or corrosive substances.
- Avoid excessive abrasion.
- Compatibility with other equipment must be verified by the user.
- Repair or modification of this product without manufacturers consent is strictly forbidden.

PMI LIMITED WARRANTY

PMI products are warranted to the original retail purchaser to be free from defect in material and workmanship for a period of one year. PMI will repair or replace the item without charge provided inspection at our factory discloses no misuse or alteration, which, in our judgment, has affected the condition or functioning of the product. All implied warranties imposed by law in connection with the sale of PMI products are also limited in duration to a period of one year. PMI expressly excludes and shall not be liable for any consequential damages arising out of any breach of the express or implied warranties on sales of PMI products. Because of the high risks involved in high angle rope work such as, but not limited to, rescue, rope access, caving, rappelling, rock climbing and mountaineering, no further warranties exist or are implied by PMI. Regulations issued under the Magnuson-Moss Warranty Act require us to include the following statement: some states do not allow limitations on how long an implied warranty lasts nor the excluding or limitation of incidental or consequential damages, so the above limitations may not apply to you.

