

This anchor can be removed and reused at any desired location. It features unmatched safety, ease of use, and speed. The RB Anchor works in horizontal, vertical, and overhead/ceiling surfaces. Costly engineering inserts are not required. This anchor can be used for fall protection, restraint, work positioning, and more. This product is designed for use in concrete or rock only.

**Key Features:**

- Spring is zinc plated steel
- Swage is zinc plated copper
- Trigger is aluminum alloy
- End termination, spoons, and stop sleeves are stainless steel
- Main cable is 7 x 19 galvanized cable

**3/4" Fall Protection RB Anchor**

*Weight: 8.0 oz (227 g) » MBS: 22 kN (5000 lbf)*  
*Length: 11.50" (29.3 cm) » Width: 2.00" (2.1 cm)*

HD26223

★ USA MADE ★ COMPLIANT ANSI Z359.1 (2007) EN 795

**1" Fall Protection RB Anchor**

*Weight: 1.00 lbs (454 g) » MBS: 44 kN (10000 lbf)*  
*Length: 13.75" (34.9 cm) » Width: 2.00" (2.1 cm)*

HD26224

★ USA MADE ★ COMPLIANT ANSI Z359.1 (2007) EN 795



A large, empty rectangular box with a thin black border, intended for handwritten notes or a drawing.

Pigeon Mountain Industries, Inc. | PO Box 803, LaFayette, GA 30278 | Fax: 706-764-1531 | Email: [custserv@pmirope.com](mailto:custserv@pmirope.com)