

These SMC Pulleys are the mini of minis. Efficient and lightweight, its solid strength and efficiency tests to greater strengths than other pulleys in the same size and price range. It has the required prusik minding capability for use in a haul system (JRB Pulleys are now incorporated in our 4:1 Kit. A 1.20" nylon sheave and zinc-coated axle make any system run smooth. Simple to use and easy to carry into the field. Max Rope diameter for the CR is 13 mm. Max rope diameter for the JR and JRB is 9 mm. The CR pulley is a single pulley, while the JR and JRB pulleys are double pulleys.

**Key Features:**

Nylon sheave • Precision machined aluminum side plates • Zinc coated axle • Rotating side plates • JRB becket  
 MBS: 2,298 lbf (13 kN)

**JR**

*Height: 1.56" (4.0 cm) » Width: 1.75" (4.4 cm) »  
 Length: 2.84" (7.2 cm) » Weight: 3.2 oz (89 g) »  
 MBS: 22 kN (5000 lbf) » Tread: 0.83" » Axle: Zinc Coated »  
 Sheave Material: Nylon » Sheave: 1.20" » Max Rope Size: 9 mm*

Blue (top left)                      SM159300  
 Black (top right)                      SM159301

★ USA MADE ★    BERRY COMPLIANT    CERTIFIED    UIAA 127 EN 12278



**JRB**

*Height: 1.56" (4.0 cm) » Width: 1.75" (4.4 cm) »  
 Length: 3.57" (9.1 cm) » Weight: 3.3 oz (94 g) »  
 MBS: 22 kN (5000 lbf) » Becket MBS: 13 kN (2923 lbf) »  
 Tread: 0.83" » Axle: Zinc Coated » Sheave Material: Nylon »  
 Sheave: 1.20" » Max Rope Size: 9 mm*

Blue (bottom left)                      SM159200  
 Black (bottom right)                      SM159201

★ USA MADE ★    BERRY COMPLIANT    CERTIFIED    UIAA 127 EN 12278



Tools not included in Xtreme Rebuild Pack



A large, empty rectangular box with a thin black border, intended for handwritten notes or technical drawings.

Pigeon Mountain Industries, Inc. | PO Box 803, LaFayette, GA 30278 | Fax: 706-764-1531 | Email: [custserv@pmirope.com](mailto:custserv@pmirope.com)