

Large size locking carabiners developed by SMC especially for the needs of the fire and rescue communities. Available in several different metal finishes, as well as in both NFPA (Class G) and non-NFPA versions. Black zinc coated models are ideal for tactical operations and stainless steel model is best for corrosive environments. Large gate opening fits easily over litter rails. All models have stainless gates and locking sleeves for greater strength and reliability.

### Key Features:

Original US made steel rescue carabiner • Large gate opening • Stainless steel gate and sleeve

### Standard

*Width: 2.97" (7.5 cm) » Length: 5.04" (12.8 cm) » Weight: 10.6 oz (300 g) »  
Major Axis MBS: 46 kN (10341 lbf) » Minor Axis MBS: 18 kN (4046 lbf) »  
Minor Axis MBS (Zinc Plated Steel): 16 kN (3597 lbf) » Gate Open MBS: 11 kN (2473 lbf) »  
Gate Opening: 1.20" (30.5 mm)*

Zinc Plated Steel (left)	SM21001
Stainless Steel (middle)	SM24001
Black Stainless Steel (right)	SM24007



★ USA MADE ★ BERRY COMPLIANT

### NFPA Versions

*Width: 2.97" (7.5 cm) » Length: 5.04" (12.8 cm) » Weight: 10.6 oz (300 g) »  
Major Axis MBS: 46 kN (10341 lbf) » Minor Axis MBS: 16 kN (3597 lbf) »  
Gate Open MBS: 11 kN (2473 lbf) » Gate Opening: 1.20" (30.5 mm)*

NFPA Zinc Plated Steel (left)	SM21001N
NFPA Black Zinc Plated Steel (right)	SM21007N



★ USA MADE ★ BERRY COMPLIANT CERTIFIED NFPA 1983, G

### NFPA - Heat Treated

*Width: 2.97" (7.5 cm) » Length: 5.04" (12.8 cm) » Weight: 10.9 oz (309 g) »  
Major Axis MBS: 65 kN (14613 lbf) » Minor Axis MBS: 16 kN (3597 lbf) »  
Gate Open MBS: 18 kN (4046 lbf) » Gate Opening: 1.20" (30.5 mm)*

NFPA Heat Treated Steel	SM21002
-------------------------	---------



★ USA MADE ★ BERRY COMPLIANT CERTIFIED NFPA 1983, G



A large, empty rectangular box with a thin black border, intended for handwritten notes or additional information.

Pigeon Mountain Industries, Inc. | PO Box 803, LaFayette, GA 30278 | Fax: 706-764-1531 | Email: [custserv@pmirope.com](mailto:custserv@pmirope.com)