

Just the thing for smaller ropes and lighter loads, SMC's Micro PMP's are ideal for building a mini haul rig or anywhere that a compact lightweight system is needed. Double version is designed with a becket to accommodate compound and complex pulley systems. Max rope diameter 13 mm.

**Key Features:**

Precision machined aluminum side plates and 1.38" sheaves • Sealed Ball Bearings • Double pulleys include a becket

**Single**

*Height: 1.12" (2.8 cm) » Width: 2.55" (6.5 cm) »  
 Length: 3.75" (9.5 cm) » Weight: 3.5 oz (99 g) »  
 MBS: 22 kN (5000 lbf) » Tread: 1.00" »  
 Axle: Ball Bearing » Sheave Material: Aluminum »  
 Sheave: 1.37" » Max Rope Size: 13 mm*

**Red** SM153000N  
**Black** SM153001N

  



**Double**

*Height: 1.81" (4.6 cm) » Width: 2.55" (6.5 cm) »  
 Length: 4.65" (11.8 cm) » Weight: 5.8 oz (164 g) »  
 MBS: 40 kN (8992 lbf) » Becket MBS: 20 kN (4496 lbf) »  
 Tread: 1.00" » Axle: Ball Bearing »  
 Sheave Material: Aluminum » Sheave: 1.37" »  
 Max Rope Size: 13 mm*

**Gold** SM154000N  
**Black** SM154001N

  



A large, empty rectangular box with a thin black border, intended for handwritten notes or technical drawings.

Pigeon Mountain Industries, Inc. | PO Box 803, LaFayette, GA 30278 | Fax: 706-764-1531 | Email: [custserv@pmirope.com](mailto:custserv@pmirope.com)