

SMC/RA 4" Dbl Pulley SS Side-Plates Oilite NFPA-G



Based on Russ Anderson's original design, these pulleys are essential equipment for the serious rigger. Rotating side plates allow attachment of the pulley anywhere on the rope and the 3" and 4" models will accept multiple carabiners. Axle nuts are marked with a blue witness line to indicate if the axle nut has been tampered with or turned.

Key Features:

- UL Certified to NFPA1983 "G" General Use.
- Uses either high efficiency sealed ball bearings or durable Oilite bushings and are designed to work flawlessly under conditions that might shut down a lower quality pulley.
- Sealed ball bearings provide optimal efficiency thus reducing the performance robbing resistance inherent in most multiple component systems and are not prone to failure under misaligned loads or with twisted gear as may occur with needle bearings.
- Matched double-bend side plates help eliminate compression under load.
- The axle-nuts are double locked to the steel axle and marked with a witness line to help detect any loosening.
- Made in the USA.

SMC/RA 4" Dbl Pulley SM157000

Manufacturer	SMC
Material	Stainless Steel
Axle	Oilite
Sheave Material	Aluminum
Sheave	4.00"
Tread	3.33"
Max Rope Size	16 mm
MBS	63 kN (14163 lbf)



Height	6.1 cm(2.40")
Length	25.1 cm(9.90")
Width	11.7 cm(4.60")
Weight	1.142 kg(2.52 lbs)

COMPLIANT NFPA 1983 (2017), G

Certified by Underwriter's Laboratories to exceed the NFPA 1983 "G" - General Use requirement of 40kN.

