

Instructions > PMI FAST Lock



MAINTENANCE AND CARE

Proper maintenance of the FAST Lock is essential to its performance

- System may be stored attached to the litter or loosely packed in a container
- Store in a clean, dry environment
- Wet components should be thoroughly dried before storage
- As with all webbing products, avoid exposure to direct flame, high temperature, chemicals or damaging substances
- PMI FAST Restraint may be hand washed in cool water. Use clear water or a non-detergent cleanser, rinse thoroughly and dry completely before storing.

Remove the PMI FAST Lock Restraint from service and destroy it if it does not pass inspection or if there is any doubt about its safety or serviceability, or if:

- The unit or its components have sustained a significant impact
- The load bearing components of the unit are damaged in any way
- The webbing shows excessive wear, is cut, is improperly rigged, or is otherwise affected in a way that might affect function or performance
- Buckles or attachment points do not function properly, or show signs of excessive wear or damage that might affect function or performance
- If the unit has been visibly damaged by heat, chemical or other hazardous condition
- If the unit has been in use for 5 years, regardless of condition

WARNING

- YOU COULD BE KILLED OR SERIOUSLY INJURED IF YOU DO NOT READ AND UNDERSTAND THIS BOOKLET BEFORE USING PRODUCT.
- SPECIAL TRAINING AND KNOWLEDGE ARE REQUIRED TO USE THIS PRODUCT.
- YOU MUST THOROUGHLY READ AND UNDERSTAND ALL MANUFACTURERS INSTRUCTIONS BEFORE USE.
- USE AND INSPECT THIS PRODUCT ONLY IN ACCORDANCE WITH THE MANUFACTURERS INSTRUCTIONS.
- YOU CAN CONTACT THE MANUFACTURER AT 706-764-1437 FOR IMPORTANT SAFETY INFORMATION.

The PMI FAST Lock pre-installed in your litter allows you to lash in a patient in a fraction of the time it takes the traditional way. Color coded shoulder and leg straps hold the patient securely, while wide stirrups hold them toward the head. A quick secure connection is also provided when a connection to a seat harness is needed. Individual straps can be quickly repositioned in the field to accommodate patient injuries. Locking (rated) carabiners mean a secure connection. You will be amazed at the speed and functionality of the PMI FAST Lock.

PE42059U

Weight: 3.85 lbs (1.75 kg)

INSPECTION

Inspect the unit prior to each use, particularly noting the condition of load bearing buckles and components. Inspection criteria should be established by the user according to his needs, and must consider at least the following hazards:

- Missing or torn components
- Improperly functioning buckles or attachment points
- Webbing and/or stitching that shows excessive wear
- Chemical damage or exposure
- Heat damage

WARNING

Failure to comply with the instructions and information contained in this booklet may result in injury or death.

WARNING

Proper training is required before use. Read these user instructions and retain them as a permanent record, and maintain a copy with the with the product use and care record.

A use and care record should be established and maintained by the purchaser or user according to their needs, and should include records specific to the item.

Specific information to note would include date of purchase; date put into service; maintenance and inspection records. Refer to this information before and after each use. The user of this equipment assumes all responsibilities associated with its use.


PMI LIMITED WARRANTY

PMI products are warranted to the original retail purchaser to be free from defect in material and workmanship for a period of one year. PMI will repair or replace the item without charge provided inspection at our factory discloses no misuse or alteration, which, in our judgment, has affected the condition or functioning of the product. All implied warranties imposed by law in connection with the sale of PMI products are also limited in duration to a period of one year. PMI expressly excludes and shall not be liable for any consequential damages arising out of any breach of the express or implied warranties on sales of PMI products. Because of the high risks involved in high angle rope work such as, but not limited to, rescue, rope access, caving, rappelling, rock climbing and mountaineering, no further warranties exist or are implied by PMI. Regulations issued under the Magnuson-Moss Warranty Act require us to include the following statement: some states do not allow limitations on how long an implied warranty lasts nor the excluding or limitation of incidental or consequential damages, so the above limitations may not apply to you.

ASSEMBLY

Each PMI FAST Lock System comes with the following components:

- Yellow patient attachment strap (A)
- Blue securing strap with ANSI buckle (B)
- Blue carabiner straps - 2 (C)
- Blue O-ring strap (D)
- Green shoulder strap (E)
- Red shoulder strap (F)
- Orange securing strap with ANSI buckle (G)
- Orange carabiner straps - 2 (H)
- Orange O-ring strap (I)
- Black foot loop system including 2 buckles (J, K)




RIGGING

One advantage of the PMI FAST Lock System is that girth-hitched attachment points can easily be relocated “up or down” on the litter in the field as needed to accommodate varying sizes of patients or other special considerations.


- BEFORE putting the patient into the litter unsnap all the carabiners and arrange the straps outside of the litter.
- Position the patient as needed in the litter.
- Place the openings in the foot loops over each of the patient’s feet so that the bottoms are snug in the middle of the patient’s feet. Then pull or loosen the tail of webbing to adjust to the desired height.
- Bring the Green and Red Straps over the patient’s shoulders and across the chest to the opposite side hip so that they clip back into the buckle on the same color strap. Adjust the tails of these straps to provide the desired tension and fit. (Fig. 1)
- At the patient’s chest, pull orange webbing over and attach to orange carabiner straps. Proceed with blue webbing to blue carabiner straps, making sure to lock each carabiner. Adjust the tails of these straps to provide the desired tension and fit. (Fig. 2)
- Use the yellow strap to connect the patient’s harness to the litter with a carabiner or by threading the yellow strap through the waist and leg loops of the patient’s harness. (Fig.3)
- Tuck away all the extra length of straps (tails) to prevent possible



(Fig. 1)



(Fig. 2)



(Fig. 3)

ADDITIONAL INFORMATION

For additional information about this or other PMI products, contact us.

Pigeon Mountain Industries, Inc.
PO Box 803
LaFayette, GA 30728

Toll Free: 888.764.1437
Phone: 706.764.1437
Fax: 800.952.3747 or 706.764.1531
Email: care@bealpmi.com
Web: www.pmirope.com

